



INFORMATION
SECURITY

INTIMUS XL 17.00 / XLM 17.00 SMARTSHRED

HIGH PERFORMANCE
MODULAR SHREDDING
SYSTEM

- ▶ For customised solutions
- ▶ Model XLM: with integrated magnetic separator



Picture similar

HIGH
PERFORMANCE
MODULAR
SHREDDING
SYSTEM

This concept assures fulfilment of your requirements and provides you with performance reserves at favorable attractive investment costs.

Competent contact persons are available to provide you with accurate advice and assistance for all of your questions and concerns. Many years of experience enable us to offer quick, efficient solutions which fulfil your individual requirements.


Each project is implemented in a clear-cut, logical fashion, allowing you to follow the development of your shredder in detail, and issue manufacturing approval with confidence.

XL 17.00 FEATURES



- Shreds paper and cardboard
- Two shredding steps: From primary shredder – 30 mm strip cut – particles fall onto a conveyor belt and are transported directly to the cutting shafts of the security shredder.
- Automatic feed of material to pre-shredder via large feed conveyor and hopper
- PLC-control with touchscreen
- Precision cutting cylinders made from special hardened steel allow for high through-put volumes with minimal wear and low power consumption
- Specially suited storage and compacting equipment is recommended for further processing of shredded particles. Simple storage solutions (containers), as well as specially configured compacting equipment for volume reduction can be supplied upon request.

XLM 17.00 FEATURES

- Shredder features see Model XL 17.00 SmartShred
- XLM shredders are equipped with an integrated magnetic separator. Obsolete ring binders, patient files and other records with metal reinforcements for hanging file folder cabinets no longer need to be sorted out for removal of integrated metal components.
- Scrapped metal parts are collected in a mobile receptacle, from which they can be disposed of.



Picture similar

SPECIFICATIONS		
Model	XL 17.00	XLM 17.00
Shred size	6 x 15-50 mm	6 x 15-50 mm
Number of Users	70+ persons	70+ persons
Security level DIN 66399	P-3/ 0-3 / T-3* / E-2	P-3/ 0-3 / T-3* / E-2
Throughput**	600 kg/Std.	600 kg/Std.
Motor power	15,8 kW	16,5 kW
Also shreds:		
Fusing:	63 A	63 A
Dimensions (w. standard feed conveyor):		
In-line set-up (WxDxH)	520x100x270 cm	620x115x310 cm
Angular set-up 90° (WxDxH)	420x220x270 cm	500x300x325 cm



400/3 Ph



3*
*or 1,000
hours

* only floppy discs /ID cards

** theoretical average

 = certain small format items - such as SSD - may go through the cutting mechanism undestroyed